



**TODO**

**EMICO**  
**WHEATON**  
by Gardner Denver

**Catalogue**

**The TODO range of products forms a vital part of Emco Wheaton's portfolio, with its reputation of being the market leader in the DRY-BREAK industry. Used globally in the most demanding conditions and designed to handle a huge range of oils, gases and hazardous chemicals, the TODO range of equipment has been setting the standard for more than 40 years.**

The TODO name has become synonymous with quality alongside Emco Wheaton's wide reaching product range of Marine Loading Arms, Distribution Loading Arms, petroleum and chemical road tanker equipment and range of refuelling systems used to refuel fleets of buses and other industrial vehicles.

Our manufacturing plants in Houston Texas, USA; Oakville Ontario, Canada; Kirchhain, Germany and Margate, UK are supported by sales offices in Paris, France; Kuala Lumpur, Malaysia; Manama, Bahrain; Vienna, Austria; Shanghai, China; Moscow, Russia and Campinas, Brazil, as well as a network of trusted distributors covering more than 100 countries globally.



# Contents

<b>2</b>	TODO-MATIC
<b>4</b>	TODO-GAS
<b>6</b>	TODO Break-Away
<b>7</b>	Collar Release Break-Away
<b>7</b>	Marine Break-Away
<b>8</b>	PTC – Safety Pressure Tight Cap
<b>9</b>	Aviation Couplings
<b>10</b>	Ball Valves
<b>11</b>	Fuel Nozzles
<b>12</b>	Swivels

## Certificates and Standards

TODO-MATIC couplings carry the highest level of certification and approvals available worldwide:  
VdTÜV under test approval mark TÜ.AGG.162-93 towards ADR, RID, IMDG and TA-Luft classifications.  
European directives 97/23/EC (PED).  
94/9/EC (ATEX) compliant.  
EN ISO 9001:2008.  
OHSAS 18001:2007.  
E4 Automotive liquefied petroleum gas components - Other than containers.

# TODO-MATIC

## Virtually zero spillage

With more than 30 years of experience in the transportation of oil, gas and hazardous chemicals, TODO is exceptionally proud of the TODO-MATIC range of DRY-BREAK couplers. Trusted around the world to transfer highly valuable and aggressive products in the most testing conditions for loading and off-loading from road or rail, offshore rig supply, ship to shore transfer and more, TODO-MATIC sets the standard for the industry.

Higher profit margins and safety credentials are assured with the TODO-MATIC range's minimal residual loss of

product on disconnection and spillage of virtually zero. Less product leakage means more product delivered to your customers and more money for your organisation.

TODO-MATIC couplers are extremely reliable, with very few moving parts and require little operator intervention which reduces the risk of human error. Customers enjoy dramatically improved operational and fugitive emission performance as well as peace of mind that all products meet the highest safety standards including European directives 97/23/EC (PED) and 94/9/EC (ATEX).

---

## 1" TODO-MATIC DRY-BREAK

(DN19 - DN32, Ø56 mm)

- Specifically designed for small bore applications
- One-handed operation
- High flow rate
- Minimal release on disconnection
- Additional option of selectivity to prevent product cross-contamination



## 2" TODO-MATIC DRY-BREAK

(DN40 - DN50, Ø70 mm)

- Suitable for diverse range of applications
- Available in range of materials and configurations
- Provides rapid, safe transfer



## 2.5" TODO-MATIC DRY-BREAK

- Ideal for road tanker and aviation applications
- Suitable to transfer a variety of liquids and vapours
- Strong integral swivel
- Ergonomic design
- Rugged construction





### 3" TODO-MATIC DRY-BREAK

- Typically used for rail and road loading/discharge
- Tough construction
- Ergonomic design
- High flow rate
- Zero spillage
- The natural choice for N.A.T.O refuelling standardisation



### 4" TODO-MATIC DRY-BREAK

(DN100, Ø164 mm)

- The most compact, lightweight high flow 4" self-sealing coupling system on the market
- Applications include:
  - off-shore ship to rig transfer of fuels and drinking water
  - aviation fuel bunkering
  - rail tank loading/discharge
  - chemical transfer
- Rapid connection and disconnection



### 6" TODO-MATIC DRY-BREAK

- Ideal for ship or barge to shore connection
- Significantly faster transfer than any flange coupling
- Environmental standards compliance
- Provides real turn-around time savings
- Rotating lifting loop as standard



### Dust plugs and dust caps

- Prevent ingress of dirt and water
- Sizes: 1" – 6"
- Available in:
  - Stainless steel, brass/gunmetal, aluminium and rubber



# TODO-GAS

## Designed for the safe transfer of LPG in both liquid and vapour phases

Improve profit margins, environmental credentials and operator safety when transporting liquid petroleum gas with TODO-GAS couplings. Specifically designed for the safe transfer of LPG, particularly propane and butane, TODO-GAS couplings comprise materials ideal for the unique properties of LPG and terminal handling properties.

The unrivalled technology in TODO-GAS couplings provide real savings as connection and disconnection are exceptionally quick, increasing turnaround, and product

loss is reduced to virtually zero. This means more product at the final destination and higher profit margins. The possibility of operator freeze burns is also removed.

Environmental regulations are increasingly important and strict but the TODO-GAS couplings can help you plan for the future. An unrivalled 99% typical reduction in emissions compared to existing thread based coupling means even the most stringent environmental standards in the world are easily matched and future changes are unlikely to affect your organisation.

---

## 1" TODO-GAS

(DN19 - DN32, Ø56 mm)

- Suitable for a range of LPG applications
- Heavy duty autogas vehicle refuelling
- Advanced vapour recovery systems
- Easy to connect and disconnect
- Single handed operation
- Ultra-low release on disconnect: 0.15cc per disconnection
- Suitable for indoor fuelling
- Handles up to 200litres/minute (52 USG/MIN)
- Minimal pressure drop



## 2" TODO-GAS

(DN40 - DN50, Ø71 mm)

- Ideal for bobtails or immediate bulk delivery trucks
- Rugged construction
- Suitable for frequent use
- Can cope with almost any loading equipment configuration
- Ultra low release on disconnect: 0.35cc per disconnection



### 3" TODO-GAS


(DN80, Ø119 mm)

- Unrivalled suitability for larger or high flow rate applications
- Typically used for rail tank loading and discharge
- Handles flows of up to 2,500 litres/minute (658 USG/MIN)
- Two handle operation
- Robust integral swivel
- Designed to withstand regular use at terminal



### Dust Plugs and Dust Caps

- Prevent ingress of dirt or water
- Materials:
  - 1" and 2" sizes: rubber
  - 3" size: stainless steel, brass/gunmetal and aluminium



### Accessories and Specials

#### Pressure relief valve for tank unit

- Dissipates trapped fluid pressure into hose unit without spillage
- Allows easy connection



#### Parking device

- For safe and convenient storing of hose units



#### Long double handle 2"

- Provides more ergonomic use of couplings



# TODO Break-away

## Cut down on accidents, cut down on costs

Save money on damages and fuel spillage while ensuring operator safety with TODO Break-away couplings. This range is designed to remove the possibility of drive away/pull away incidents when a tanker moves without having first disconnected from the terminal.

With these kinds of incidents happening more often than one might imagine, and with the potential to cause serious

damage and put operators at risk, TODO Break-away couplings mean that human error is no longer a factor. Should the tanker pull away, the coupling automatically senses the issue and closes the valve before allowing the main valve to safely release. This ensures no product is released or spilt and neither the coupler, terminal nor tanker incur any damage.

Take out the risks, choose TODO BREAK-AWAY.

---

## Features

- Exceptionally high flow rate / low pressure drop
- Extremely quick closing time
- Minimum loss of product
- Simple and safe design, with reduced numbers of components
- Easy to handle
- Easy to maintain and repair
- Suitable for a wide range of applications

## 2" TODO Break-Away

(DN50)

- Extremely quick closing time
- Minimum loss of product
- Suitable for a wide range of applications

## 3" TODO Break-Away

(DN80)

- Extremely quick closing time
- Minimum loss of product
- Suitable for a wide range of applications





# Collar Release Break-Away

## Eliminate spillage

The TODO Collar release Break-Away Coupling is new to the TODO range and offers an alternative to the standard range serving a very different purpose. Like the standard product it has been designed to eliminate spillage and damage associated with drive and/or pull away incidents when loading and unloading hazardous liquids, but with the added benefits of safeguarding loading arms.

When used with loading arms the break-away is engineered to disconnect if the arm travels past the customer designated breakage position. The collar is linked via break cable to the loading arm so that once the break position is reached, the collar splits, shutting the valves off. In addition to reducing any potential environmental impact from a break, the loading arm is safeguarded and potential costly downtime is avoided.

## 2" & 3" Collar Release Break-Away

(DN50) & (DN80)

- High flow rate/low pressure drop
- Operates independently of shut off safety systems and does not require an external power source
- Will release at any angle of pull
- Easy to re-set on site



---

# Marine Break-Away

## Eliminate spillage and damage associated with ship and/or barge movement

The TODO Marine Break-Away Coupling has been designed to eliminate spillage and damage associated with ship and/or barge movement when loading and unloading hazardous liquids.

The Marine version of TODO's tried and tested Standard Break-Away Coupling has a more robust design and has been engineered to withstand harsh marine conditions.

The coupler identifies an excessive load, closes the valves and then allows disconnection.

## 4" Marine Break-Away

(DN100)

- High flow/low pressure drop
- Designed to resist axial force so that disconnect only occurs when subjected to straight pull forces
- Operates independently of shut off safety systems and does not require an external power source
- Easy to re-set on site



# TODO Safety Pressure Tight Cap

## Protect your operators and your profits

Designed in close collaboration with leading gas and oil companies, the TODO Safety Pressure Tight Cap is designed with the needs of businesses in mind. Containment security and operational safety are two of the biggest concerns in the industry and both of these are assured with the TODO Safety Pressure Tight Cap.

Companies are assured better safety credentials and operational benefits when using the TODO Safety Pressure

Tight Cap. No other existing closure technology comes close.

The cap will sense when the event of an upstream closure leakage is possible and will hold any pressure necessary until the problem is resolved. If the cap should be removed for any reason, it will quickly decrease the pressure to avoid forceful transfer of the media. This will improve profits and prevent operators from coming to harm.

---

## Features

- Pressure indicator alerts the operator to pressure above 1.0 bar behind the cap & possible failure of upstream closure
- Automatic depressurisation
- Reduces static pressure upstream of the cap
- Removes the possibility of disconnecting the cap whilst under pressure avoiding injury
- Customs / tamper seal feature
- Suitable for use with all commonly used wire and plastic custom seals
- Automatic locking with manual locking available
- Certified closure
- Certified as a full second or third closure depending on the application
- The cap can be used to replace other closure methods such as valves

## 2" PTC

(DN 50)

- Compact for smaller applications
- Alerts operator to pressure above 1.0 bar
- Prevents disconnection of cap while under pressure to avoid injury
- Certified as a full second or third closure depending on the application

## 3" PTC

(DN 80)

- Alerts operator to pressure above 1.0 bar
- Prevents disconnection of cap while under pressure to avoid injury
- Certified as a full second or third closure depending on the application

## 4" PTC

(DN 100)

- Alerts operator to pressure above 1.0 bar
- Prevents disconnection of cap while under pressure to avoid injury
- Certified as a full second or third closure depending on the application



2" (DN 50) PTC



3" (DN 80) PTC



4" (DN 100) PTC

# Aviation Couplings

## The economical alternative for aviation fuelling

TODO Aviation couplings represent real money savings as well as improved safety features and exceptional ease of use to organisations involved in the aviation industry. With all valves guaranteeing closure before disconnection, reducing spillage, the product is not wasted resulting in higher profit margins.

The TODO Aviation couplings' unrivalled reliability and robust design mean that maintenance and replacement costs are lowered. Meanwhile, simple operation reduces human error and improves turnover time.

The range includes the TODO-45 coupling – the first economic alternative to the ISO 45 under wing hose couplers – and the TODOMATIC aviation hydrant connection.

---

## TODO-45

- Economical alternative to ISO 45 standard hose couplers
- Automatic valve opening on connection and disconnection
- Simple single action operation, no levers or switches
- Guaranteed valve closure prior to disconnection
- Minimal residual loss on disconnection
- Will connect and disconnect under pressure and flow where necessary
- Extremely reliable with very few moving parts
- Robust construction: no external operational components



## TODO-MATIC aviation hydrant

- Integral over pressure relief valve.
- Dissipates trapped fluid pressure into hose coupler without spillage
- Allows easy connection
- All TODO-MATIC couplings are available in aviation fuel transfer specifications



# Ball Valves

## Lightweight valves, heavyweight performance

TODO'S lightweight ball valves offer real cash savings through significant weight savings to the road and tanker industry. Designed to work specifically well in any application which involves regular compartment switching, the ball valves are also used in fixed plant and mobile refuelling applications.

The unrivalled sandwich design ensures that quick, easy valve changeover is permitted with a PTFE seal preventing

leakage – all of which help to save businesses time and money. The robust construction, with very few moving parts, results in a highly reliable system.

One-way and two-way valves are available, each with the same benefits to your business or organisation. All TODO ball valves meet the highest international standards for safety and have TDT approval, mark TDT-UW-30/09, are manufactured under EN ISO 9001:2000 and are certified towards ISO 14001:2004 and OHSAS 18001:2007.

---

## Features

- Aluminium valve body and ball
- Easy to service
- PTFE ball sealing
- Operate under pressure and flow
- Extremely reliable
- Robust construction
- Available with handle or actuator
- Sizes: 2" (DN 50) - 4" (DN 100)
- Working Pressure: PN 10
- Safety factor: 5:1

## One way ball Valves

Ideal for use in road tankers and a variety of plant applications to permit flow in one direction only, TODO one way ball valves are available with pneumatic actuator and with a wide selection of end connectors.

### The Range:

- 4" ball valve with actuator
- 3" ball valve
- 2" ball valve

## Two way ball valves

The two way ball valves range offers the same benefits as the one way valves with a different function. Ideal for use as a compartment or tank switching valve, the two way ball valves control the direction of flow between either of two outlets.

### The Range:

- 4" ball valve
- 3" ball valve with actuator
- 2" ball valve



# TODO Fuel Nozzles

## Total delivery: total security

TODO fuel nozzles are specifically designed to withstand the pressure of high volume delivery from tanker to the loading station of product in complete safety. The world-leading technology ensures the handle locks when in the closed position and coupled with the ergonomic design of all the nozzles, ensures that loss of product through human error is significantly reduced. This plus the high flow rate which shortens turnaround time will ensure more product delivered in quicker time meaning higher profits for your organisation.

Maintenance and replacement costs are reduced thanks to the robust manufacture and reliability of the TODO fuel nozzles. Long-term performance is assured in the aluminium alloy body and PTFE Teflon seal.

Operator safety is always key and, with less product lost on disconnection and through human error, TODO fuel nozzles are designed to reassure all of our customers they are in safe hands. As with all TODO products, the highest safety standards worldwide are met including TDT approval, mark TDT-UQ-30/09, ADR/RID in Poland, manufactured under EN ISO 9001:2000 and carrying the certificate ISO 14001:2004 and OHSAS 18001:2007.

## Features

- Available with or without anti drain valves
- Automatic handle locking when in closed position
- Optional threaded sight glass
- High flow
- Ease of use
- Ballsealings in PTFE (Teflon®) as standard
- TODO-SNAP lug nut equipped on request
- Size: 1½" (DN 40)
- Aluminium alloy components
- Working pressure: PN 10
- Safety factor: 1:5

## Nozzles Range:

- TW fuel nozzle
- Male/male fuel nozzle
- Male/female fuel nozzle

## Accessories Range:

- TODO-SNAP lug nut with 45° bend
- Sight glass
- Dust plug
- Hook spanner
- TODO-SNAP lug nut
- Outlet with extra-long swivelling lug nut
- Spout
- Lug nut tool





# TODO Swivel

## Improved reliability, improved manoeuvrability

One of the biggest causes of premature hose failure – and therefore maintenance costs and wasted time – is torque stress imparted onto the assembly hose by permitting free hose movement. The leading technology in the TODO Swivel avoids this stress, allowing the hose to relax to its natural rest position, whilst permitting free movement of the hose.

Having been used in the toughest applications worldwide for 20 years, organisations can rest assured that the TODO Swivel will give them ease of use with the highest safety credentials. Available in a range of materials, sizes and compact in design, it is ideal in a range of applications.

The TODO swivel meets the highest safety requirements worldwide including TDT approval, mark TDT TDT-UW-30/09, ADR/RID in Poland, manufactured under EN ISO 9001:2000 and ISO 14001:2004 and OHSAS 18001:2007.

---

## Features

- Simple design
- Low maintenance
- Highly reliable
- Very compact
- High flow rate / low pressure drop
- Features stainless steel bearings and single o-ring seal
- Available in sizes from ¾" (DN19) to 4" (DN100)
- Full range of materials: Aluminium, gunmetal/brass and 316L stainless steel
- FPM (Viton®) seal fitted as standard – full range of elastomeric seals available
- Working pressure: 1", 2", 2½", 3" stainless steel PN 25 bar. Others PN 10 bar.

## TODO Swivel Range:

- 4" BSP Female – male
- 3" Flange – BSP – male
- 2½" BSP female – male
- 2" BSP male – NPT female
- 1½" BSP male – female
- 1½" BSP male – male
- 1" BSP male – female





2

3

4

5

6

7

8

9

10

# EMCO WHEATON

by Gardner Denver

## MANUFACTURING FACILITIES

### Emco Wheaton

Channel Road,  
Westwood Industrial Estate,  
Margate,  
Kent,  
CT9 4JR UK  
Phone +44 (0)1843 221521  
Fax +44 (0)1843 295444

### Emco Wheaton Corp.

2390 South Service Road West,  
Oakville,  
Ontario,  
L6L 5M9  
CANADA  
Phone +905-829-8619  
Fax +905-829-8620

### Emco Wheaton GmbH

Emcostraße 2-4,  
35274,  
Kirchhain,  
Germany  
Phone +49 6422 84-0  
Fax +49 6422 5100

### Emco Wheaton USA, Inc.

9111 Jackrabbit Road,  
Houston,  
Texas,  
77095  
USA  
Phone +1 281 856-1300  
Fax +1 281 856-1325

## SALES OFFICE

### Emco Wheaton

Channel Road,  
Westwood Industrial Estate,  
Margate,  
Kent,  
CT9 4JR UK  
Phone +44 (0)1843 221521  
Fax +44 (0)1843 295444

### Emco Wheaton Corp.

2390 South Service Road West,  
Oakville,  
Ontario,  
L6L 5M9  
CANADA  
Phone +905-829-8619  
Fax +905-829-8620

### Emco Wheaton GmbH

Emcostraße 2-4,  
35274,  
Kirchhain,  
Germany  
Phone +49 6422 84-0  
Fax +49 6422 5100

### Emco Wheaton USA, Inc.

9111 Jackrabbit Road,  
Houston,  
Texas,  
77095  
USA  
Phone +1 281 856-1300  
Fax +1 281 856-1325

### Emco Wheaton France

Emco Wheaton Division  
Immeuble le Miroir  
15-17 Bld du Général De Gaulle  
92542 Montrouge Cedex  
France  
Phone +33 1 46 12 41 41  
Fax +33 1 46 12 41 61

### Emco Wheaton GmbH

Blue Danube Park,  
Objekt 60,  
2100 Korneuburg,  
Austria  
Phone +43 2262 64281-0  
Fax +43 2262 6428120

### Emco Wheaton GmbH

Presnenskaya emb. 10  
Block C – Embankment Tower – of. 526  
123317 Moscow  
Russia  
Phone +7 495 9677612  
Fax +7 495 9677600

### Emco Wheaton Asia Pacific

21-5F IOI Business Park, Bandar Puchong Jaya,  
Puchong, 47170,  
Selangor, Malaysia  
Phone +603 8075 7500  
Fax +603 8075 4100

### Gardner Denver International Ltd

PO Box 30804  
Diraz, Manama  
Bahrain  
Phone +973 17813187  
Fax +973 17813186

### Emco Wheaton

Av. Mercedes Benz,  
700 - Distrito Industrial - Campinas  
13054-750 - SP  
Brazil  
Phone +55 19 3765 8303  
Mobile +55 19 98168 8516

[www.emcowheaton.com](http://www.emcowheaton.com)

[assist@emcowheaton.com](mailto:assist@emcowheaton.com) | [@EmcoWheaton](https://twitter.com/EmcoWheaton) | [www.facebook.com/EmcoWheaton](https://www.facebook.com/EmcoWheaton)